


ACC201007

COMPOSITE CABLE FOR WASHER TANKS

HAZARDOUS AREA

- COMPOSITE CABLE, 3 WIRES
- UV AND OIL RESISTANT
- MECHANICAL RESISTANT
- FLAME RETARDANT
- COLD RESISTANT



TECHNICAL SPECIFICATIONS

GENERAL & MECHANICAL

Operating Temperature	-50 ° + 90 °C (-58° +194° F) (fixed installation) -40 ° + 90 °C (-40° +194° F) (occasional flexing)
Inner sheath (cable)	Halogen free
Screen (cable)	Tinned Copper wires braid
Outer sheath (cable)	Oil Resistant - MUD Resistant - UV Resistant
Diameter (ext.)	12mm
Minimum bending radius	20 x Ø (occasional flexing) 6 x Ø (fixed installation)
Nominal weight	212kg/km

CERTIFICATIONS

Standards	NEK TS 606:2016 (Oil & Mud resistant) IEC 61892-4 (Oil & Mud resistant) VDE 0472-815 (Halogen free) IEC 60332-1-2; IEC 60332-3-22 Cat. A (Flame retardant) ISO 4892-2 (UV resistant) EN 50396 (Ozone resistant) UL 1309 (Salt water resistant)
UL approval	USA: UL AWM Style 20234 Canada: cUL AWM II A/B

CONDUCTORS

Power conductors	3 conductor, cross sectional area 1,5mm ² brown, blue, yellow/green (line, neutral, earth)
-------------------------	--

MODELS

ACC201007	Mechanically robust cable for connection between washer system and junction box. Sold by the meter
------------------	--

ACCESSORIES

CGK201007	Explosion-proof cable glands kit (1x ½" NPT for washer system solenoid valve side, 1x M20 for JB side) for ACC201007 cable
------------------	--